

1



**PIC-D4153IF-PW2-A**



IP CAMERA **ECO**  
5 Megapixel 1.3" Starlight CMOS Sensor  
Main Stream **5.0MP** @25fps  
2880\*1620Resolution  
Encoding H.+265/H.264,Dual Stream  
3.6MM Starlight Fixed Lens  
DWDR, 3DNR, BLC,HLC  
30M Warmlight, **4 EXIR LED**  
Built In Mic /Smart POE/12VDC  
Human Bodydetection  
**H2P Chipset/Ip66 Metal/Standard Onvif**  
ECONOMIC

17.900.000 IRR

جزئیات محصول

2



**PIC-D4154HF-PW2-A**



IP CAMERA **ECO**  
5 Megapixel 1.3" Starlight CMOS Sensor  
Main Stream **5.0MP** @25fps  
2880\*1620Resolution  
Encoding H.+265/H.264, Dual Stream  
3.6MM Starlight Fixed Lens  
DWDR, 3DNR, BLC, HLC  
40M Warmlight, **6 EXIR LED**  
Built In Mic/Smart POE/12VDC  
Human Body Detection  
**H2P Chipset/IP66 Metal/Standard ONVIF**  
ECONOMIC

17.900.000 IRR

جزئیات محصول

3



**PIC-DIS3324-WAP**



IP Camera **Easy67**  
2.4Megapixel  
1/2.9" Starlight CMOS Sensor  
2.8mm F1.6 Starlight Fixed Lens  
25FPS-(1920\*1080) **Resolution 2MP**  
Encoding H.265+/264 Dual Stream  
DWDR, 3DNR, BLC,HLC  
**50M Warmlight, 4 HIGH POWER LED**  
Built-In Mic/Smart Poe/12VDC  
Human Body Detection, Perimeter, Tripwire  
Standard ONVIF Compatible With Dahua,Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/Easy Install/IP67 Metal**  
Series S  
Mobile Monitoring, VMS Monitoring, XVR View

23.900.000 IRR

جزئیات محصول

4



**PIC-BIS8924-WAP**



IP Camera **Easy67**  
2.4Megapixel  
1/2.9" Starlight CMOS Sensor  
3.6mm F1.6 Starlight Fixed Lens  
25FPS-(1920\*1080) **Resolution 2MP**  
Encoding H.265+/264 Dual Stream  
DWDR, 3DNR, BLC,HLC  
**50M Warmlight, 6 SUNNY LED**  
Built-In Mic/Smart Poe /12VDC  
Human Body Detection, Perimeter, Tripwire  
Standard ONVIF Compatible With Dahua,Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/Easy Bracket/IP67 Metal**  
Series S  
Mobile Monitoring, VMS Monitoring, XVR View

23.900.000 IRR

جزئیات محصول

5



**PIC-DIS3354-WAP**



IP Camera **Easy67**  
5.0Megapixel  
1/3" Starlight CMOS Sensor  
2.8mm F1.6 Starlight Fixed Lens  
25FPS-(2880\*1620) **Resolution 5MP**  
Encoding H.265+/264 Dual Stream  
DWDR, 3DNR, BLC,HLC  
**50M Warmlight, 4 HIGH POWER LED**  
Built-In Mic/Smart Poe/12VDC  
Human,Vehicle, Perimeter, Tripwire SMD  
Standard ONVIF Compatible With Dahua,Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/Easy Install/IP67 Metal**  
Series S  
Mobile Monitoring, VMS Monitoring, XVR View

34.500.000 IRR

جزئیات محصول

6



**PIC-BIS8954-WAP**



IP Camera **Easy67**  
5.0Megapixel  
1/3" Starlight CMOS Sensor  
3.6mm F1.6 Starlight Fixed Lens  
25FPS-(2880\*1620) **Resolution 5MP**  
Encoding H.265+/264 Dual Stream  
DWDR, 3DNR, BLC,HLC  
**50M Warmlight, 6 SUNNY LED**  
Built-In Mic/Smart Poe/12VDC  
Human,Vehicle, Perimeter, Tripwire SMD  
Standard ONVIF Compatible With Dahua,Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/Easy Bracket/IP67 Metal**  
Series S  
Mobile Monitoring, VMS Monitoring, XVR View

34.500.000 IRR

جزئیات محصول

7

**PIC-DIS3354-WAPU**



IP Camera **Easy67**  
5.0Megapixel **16:9 W**  
1/2.7" Starlight CMOS Sensor  
2.8mm F1.6 Starlight Fixed Lens  
25FPS-(2880\*1620) **Resolution 5MP**  
Encoding H.265+/264 Dual Stream  
120db WDR, 3DNR, BLC,HLC  
**50M Warmlight**, 4 HIGH POWER LED  
**Built-In Mic/Smart Poe /12VDC**  
Human,Vehicle,Perimeter,Tripwire SMD Face detection  
Standard ONVIF Compatible With Dahua, Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/Easy Install/IP67** Metal  
Series S  
Mobile Monitoring, VMS Monitoring, XVR View

**42.000.000 IRR**

جزئیات محصول

8

**PIC-BIS8954-WAPU**



IP Camera **Easy67**  
5.0Megapixel **16:9 W**  
1/2.7" Starlight CMOS Sensor  
3.6mm F1.6 Starlight Fixed Lens  
25FPS-(2880\*1620) **Resolution 5MP**  
Encoding H.265+/264 Dual Stream  
120db WDR, 3DNR, BLC,HLC  
**50M Warmlight**, 6 **SUNNY** LED  
**Built-In Mic/Smart Poe /12VDC**  
Human,Vehicle,Perimeter,Tripwire SMD Face detection  
Standard ONVIF Compatible With Dahua,Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/Easy Bracket/IP67** Metal  
Series S  
Mobile Monitoring, VMS Monitoring, XVR View

**42.000.000 IRR**

جزئیات محصول

9

**PIC-BIS9185-WAPU**



IP Camera  
8.0Megapixel **SONY IMX**  
1/2.8" Starlight CMOS Sensor  
3.6mm F1.6 Starlight Fixed Lens  
20FPS-(3840\*1620) **Resolution 8MP**  
Encoding H.265+/264 Dual Stream  
120db WDR, 3DNR, BLC,HLC  
**50M Warmlight**, 4 HIGH POWER LED  
**Built-In Mic/Smart Poe /12VDC**  
Human,Vehicle,Perimeter,Tripwire SMD Face detection  
Standard ONVIF Compatible With Dahua, Hikvision  
Tiandy, XVR Plaron, Other Devices  
**Professional Chipset/IP67** Metal/Series S  
Mobile Monitoring, VMS Monitoring, XVR View

**63.000.000 IRR**

جزئیات محصول

**10 PNV-PS8110F-4K**

10CH H.265+ Video Compression 4K (8.0MP)  
80Mbps Incoming Bandwidth  
10CH Playback (Main Stream + Sub Stream)  
10CH Live View, Up to 8.0MP Resolution for Preview & Playback  
Encode: 10\*(4K@25fps) Decode: 1\*4K@25FPS  
Support SMD and AI For 10CH  
Support Face Detection / Perimeter / Tripwire  
Support Digital Audio For 10CH  
HDMI 4K & VGA Video Simultaneous Output  
1 SATA HDD Up to 10TB  
1CH Audio Out  
3\*USB 2/0, 1\*10/100Mbps LAN  
P2P Support Iran Servers, International Servers  
IOS, Android, XVR View  
Series S



49,500,000 IRR

جزئیات محصول

**11 PNV-PS8120H-4K**

20CH H.265+ Video Compression 4K (8.0MP)  
160Mbps Incoming Bandwidth  
16CH Playback (Main Stream + Sub Stream)  
20CH Live View, Up to 8.0MP Resolution for Preview & Playback  
Encode: 20\*(4K@25fps) Decode: 2\*4K@25FPS  
Support Camera SMD and AI For 20CH  
Support Camera Face Detection / Perimeter / Tripwire  
Support Digital Audio For 20CH  
Support NVR SMD 4CH and Face Detection 4CH  
HDMI 4K & VGA Video Simultaneous Output  
1 SATA HDD Up to 10TB  
1CH Audio Out  
3\*USB 2/0, 1\*10/1000Mbps LAN  
P2P Support Iran Servers, International Servers  
IOS, Android, XVR View  
Series S



81,000,000 IRR

جزئیات محصول

**12 PNV-PS8132H-4K**

32CH H.265+ Video Compression 4K (8.0MP)  
200Mbps Incoming Bandwidth  
16CH Playback (Main Stream + Sub Stream)  
32CH Live View, Up to 8.0MP Resolution for Preview & Playback  
Encode: 32\*(4K@25fps) Decode: 4\*4K@25FPS  
Support Camera SMD and AI For 32CH  
Support Camera Face Detection / Perimeter / Tripwire  
Support Digital Audio For 32CH  
Support NVR SMD 8CH and Face Detection 4CH  
HDMI 4K & VGA Video Simultaneous Output  
1 SATA HDD Up to 10TB  
1CH Audio Out  
3\*USB 2/0, 1\*10/1000Mbps LAN  
P2P Support Iran Servers, International Servers  
IOS, Android, XVR View  
Series S



98,000,000 IRR

جزئیات محصول